

# Evanesce Series

Electric In-Ceiling Projection Screen



Compatible with Standard Throw Projectors ONLY

## Product Description

The **Evanesce Series** is a fully contained in-ceiling electric projection screen. It is encased in a white-enameled aluminum housing for convenient installation. Uses Elite's MaxWhite® FG, a fiberglass backed material for added stiffness which provides the flattest possible non-tensioned screen surface with universal applications. Control package includes Infrared & Radio Frequency remote controls along with a wall box controller and 12-volt trigger capability.



Models	Diagonal	Aspect Ratio	View Width	View Height	Material	Gain	Case Color	Top Border
IHOME106HW2-E18	106"	16:9	92.4 in	52.0 in	MaxWhite® FG	1.1	White	18 in
IHOME112HW2-E16	112"	16:9	97.6 in	55.0 in	MaxWhite® FG	1.1	White	16 in
IHOME126HW3-E20	126"	16:9	109.8 in	67.8 in	MaxWhite® FG	1.1	White	20 in

For full list of models visit [www.elitescreens.com](http://www.elitescreens.com)

## Product Features

- MaxWhite® Fiberglass, 1.1 Gain black backed matte white material
- 180° wide-viewing angle for commercial and residential presentations
- Black masking borders enhance picture contrast
- 4K Ultra HD, Active 3D, and HDR Ready
- Flame Retardant: Complies with NFPA 701 Standards
- Durable and easy to clean surface
- Disappearing recessed in-ceiling design for non-dedicated media rooms
- Below and above ceiling access installation design
- Integrated ceiling projection screen ships fully assembled, ready to install
- Available in diagonal sizes 106", 112", and 126" in 16:9 format
- Includes handheld Infrared (IR) and Radio Frequency (RF) remote controls, and a wall box controller for manual on-wall operation.
- User-friendly programmable vertical drop position for easy installation **(RC1 Version Only)**
- Wall box controller is detachable for a clean look while maintaining RF & IR functionality
- Built-in selectable channels allow one RF remote programming to control multiple screens and prevent interference **(RC1 Version Only)**
- 12v trigger feature allows the screen's UP/DOWN operation to synchronize with the projector's power cycle
  - Wired for **RC1 Version Only**
- Conforms to UL 2043 - Plenum Rated: Suitable for air-handling spaces
- 2-Year / 3-Year ENR-G Manufacturer's Warranty by Elite Screens